DEKS
Easy to Work With

WARRANTY DEKS SILICONE 35 YEAR OR EPDM 25 YEAR WARRANTY

Dektite® Original

The original watertight flashing for metal roof penetrations

Color Boots

UPC®

- **Easy to identify**
  Dektite brand name engraved on product for traceability
- **Unique cone design**
  Provides 10mm (1/2") continuous contact with flashed pipe providing a watertight seal
- **Clear markings in metric and imperial measures**
  Makes for easier cutting to pipe size
- **Proven design**
  Associated with the roofing industry globally for over 40 years
- **Size ranges: #3; #5; #8**
  Black, Grey, White, Bright Red, Brown, Terra Cotta, Dark Green, Light Green, Dark Blue, Light Blue
- **Thirty five year warranty**
  Just fit it and forget it - we've got you covered.

LAKESIDE CONSTRUCTION FASTENERS

To purchase contact us at:
***800-537-4160** (toll free)*
www.lakeside-fasteners.com

DEKS
Easy to Work With

WARRANTY DEKS SILICONE 35 YEAR OR EPDM 25 YEAR WARRANTY

Selection Guide

Grey	White	Bright Red	Brown	Terra Cotta	Dark Green	Light Green	Dark Blue	Light Blue	Black	Dektite Description	Pipe OD		Carton Quantity
											mm	inch	
DF100G	–	–	–	–	–	–	–	–	–	Original Mini	0 - 35	0 - 1 3/8”	40
DF101G	–	–	–	–	–	–	–	–	DF101B	Original #1	5 - 60	1/4 - 2 1/2”	10
DF102G	–	–	–	–	–	–	–	–	DF102B	Original #2	45 - 80	1 3/4 - 3 1/4”	10
DF103G	DF103WH	DF103BR	DF103BN	DF103TC	DF103DG	DF103LG	DF103DB	DF103LB	DF103B	Original #3	5 - 127	1/4 - 5”	10
DF104G	–	–	–	–	–	–	–	–	DF104B	Original #4	75 - 160	3 - 6 1/4”	10
DF105G	DF105WH	DF105BR	DF105BN	DF105TC	DF105DG	DF105LG	DF105DB	DF105LB	DF105B	Original #5	108 - 190	4 1/4 - 7 1/2”	5
DF106G	–	–	–	–	–	–	–	–	DF106B	Original #6	125 - 230	5 - 9”	5
DF107G	–	–	–	–	–	–	–	–	DF107B	Original #7	150 - 280	6 - 11”	5
DF108G	DF108WH	DF108BR	DF108BN	DF108TC	DF108DG	DF108LG	DF108DB	DF108LB	DF108B	Original #8	175 - 330	7 - 13”	5
DF109G	–	–	–	–	–	–	–	–	DF109B	Original #9	254 - 483	10 - 19”	2
DF606	–	–	–	–	–	–	–	–	–	Original #10	381 - 609	15 - 24”	1

EPDM will withstand constant temperatures at the roofline of -50°C (-58°F) to 115°C (239°F) and up to 150°C (302°F) intermittently.
Red Silicone will withstand constant temperatures at the roofline of -50°C (-58°F) to 200°C (392°F) and up to 250°C (482°F).
Please Note that the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.

Installation Information

1 Cut Dektite® at appropriate pipe diameter marking.

2 Slide Dektite® flashing down over pipe.

3 Apply sealant on underside of flexible aluminum base.

4 Press Dektite® base into contours of panel configuration.

5 Fasten Dektite® to surface with long -life, self drilling fasteners. Apply additional sealant around base if desired.

- Always use the neutral cure low modulus silicone for sealing
- In corrosive and coastal environments fix using LCF Long-Life ZMAX/ SC STEEL GUARD fasteners. Heads of long-life fasteners wont Red Rust!

Need to flash a tiled roof? Contact Lakeside Construction Fasteners to discuss the tile roof flashing range.