- Translucent formula makes repairs less noticeable
- 100% silicone rubber (solvent free, no odor)
- Excellent repair material for many substrates
- Rain safe in 1 hour (70°F/50% RH)
- Excellent adhesion and hang
- Easily applied with a brush or trowel
- VOC Compliant
- No hardening, chalking, crazing, or cracking
- Application temperature: -20°F to 160°F
- Service temperature: -40°F to 400°F

Perfect for emergency repairs to leaky metal roofs,

NovaFlex Metal Roof Repair & Patch Mastic

can be quickly applied with a trowel or brush, fully curing into a translucent, rubber-like solid in as little as 48 hours.

2022 METALCON TOP PRODUCT AWARD

PRODUCT SPECIFICATIONS		
Physical Property	**Test Method**	**Performance Range**
Appearance		Mastic Paste (Translucent)
Viscosity	Brookfield #7 @ 10 rpm	3,500 - 7,000 poises
Skin Over Time	3/8" @ 50% RH & 77°F	5 - 10 minutes
Through Cure	3/8" @ 50% RH & 77°F	48 hours

TYPICAL PROPERTIES*		
Physical Property	**Test Method**	**Typical Value**
Specific Gravity		1.00 - 1.05
Tensile Strength	ASTM D412	140 - 200 psi
Elongation	ASTM D412	500 - 650%
Tear Resistance	ASTM D624	30 - 35 pli
Shore A Hardness	ASTM D2240	20 +/- 5
Service Temperature		- 40°F to 400°F (- 40°C to 204°C)
Application Temperature		-20°F to 160°F (-29°C to 71°C)
Joint Sealant Designation	ASTM C920	Type S Grade NS Class 35 Use NT, M, G, A, O
Adhesion Glass Aluminum Vinyl	ASTM D903	12 - 15 pli 10 - 14 pli 12 - 15 pli

*The values outlined reflect testing that was conducted under laboratory conditions, actual results may vary. The information provided in the above table is not intended for use in preparing specifications. Please consult manufacturer for additional info.

VOC COMPLIANT ENVIRONMENTALLY RESPONSIBLE

CALIFORNIA PROPOSITION 65 COMPLIANT

COLOR CHART

MRR150 Translucent

AVAILABLE IN: 1 gallon pails

SPECIFICATIONS: Meets or exceeds ASTM C-920, TT-S-001543A and TT-S-230C.

USES: Repairing metal siding/metal roofs, gutters, chimney flashing, snow guards, pipe boots, and downspouts/trim.