- Rainproof in 1 hour (70°F/50% RH)
- Applies down to 10°F
- Will not shrink upon curing
- No mixing required
- No special tools required
- 18 month shelf life
- Solvent free, contains no isocyanates
- No outgassing or bubbling on damp surfaces (common with urethane products)
- 5 year limited warranty

A moisture curing, pourable sealant for pitch pans and other penetration seals,

NovaFlex Pitch Pocket Penetration Sealant

is semi self-leveling, while viscous enough to avoid drain-out issues, and can be applied in damp, dry, or cold climates, drying to an elastomeric, rubber-like solid.

VOC COMPLIANT ENVIRONMENTALLY RESPONSIBLE

CALIFORNIA PROPOSITION 65 COMPLIANT

PRODUCT SPECIFICATIONS

Physical Property	Test Method	Performance Range
Appearance		Flowable (Various Colors)
Viscosity	Brookfield #7 @ 10 rpm	750 - 1,250 posies
Skin Over Time	3/8" @ 50% RH & 77°F	15 - 45 minutes

TYPICAL PROPERTIES*

Physical Property	Test Method	Typical Value
Specific Gravity		1.13 – 1.15
Tensile Strength	ASTM D412	60 - 80 psi
Elongation	ASTM D412	1,200 - 1,450%
Tear Resistance	ASTM D624	12 - 17 pli
Shore A Hardness	ASTM D2240	5 +/- 2
Service Temperature		- 40°F to 400°F (- 40°C to 204°C)
Application Temperature		-20°F to 160°F (-29°C to 71°C)

COLOR CHART

MXP100 White

MXP111 Gray

MXP110 Black

AVAILABLE IN: 20 ounce sausage packs

USES: Sealing in pitch pans and other penetration seals.