RIDGE-X VENT™

40 Year Warranty!

RIDGE-X VENT™ SYSTEM:

- 18.4 Sq. In. Net Free Area / LF!
- Fits Under Any Ridge Cap!
- Adhesive Full Length & Width of Product!
- Meets All Model Building Codes: CABO, SBCCI, BOCA, ICBO!

Made in the U.S.A.

RIDGE-X VENT SECURE™

LAKESIDE™
CONSTRUCTION FASTENERS

To purchase contact us at:
1203 Goldsmith Road, Paragould, AR 72450
***870-586-0703** (office) \ **870-586-0643** (fax)*
***800-537-4160** (toll free)*
www.lakeside-fasteners.com

2-2023_V14

Your Low In-Place Cost Solution!

RIDGE-X VENT™

Description: 2-1/2" W x 1" H x 20' L (1 Pack 40' LF)

Size: Panel Profiles from 1/2" up to 1"

Metal Roof: Ridge Vent; Rake; Hip; Valley

Shingle Roof: Ridge Vent; Soffit; Rake

Innovation: Full Adhesive Strip
Patented UV & Antimicrobial Coating

Material: Non Woven Polyester Fiber

Made from over
90% recycled fiber;
over 30% post-consumer content.

The **Ridge-X Vent™** by Lakeside Construction Fasteners offers installers and contractors a low in-place cost venting solution for metal and shingle roofs! The design of the **Ridge-X Vent™** non woven polyester fiber structure inhibits water, dirt, and snow from penetrating the building structure. **Ridge-X Vent™** promotes positive air ventilation throughout the building envelope which starts at the ridge cap! The special formulated UV Coating allows the **Ridge-X Vent™** to resist high temperature environments, and prevents the fiber structure from collapsing!

Specifications

Air Permeability	760 Cubic Feet per minute
Heat Resistance	325˚F (163˚C) for 550 hours
Cold Crack	-130˚F (-55˚C)
Snow Infiltration	0
Tensile Strength	25 PSI – Elongation 150%
Attic Ventilation	Meets UBC Code
Dust Exposure	No Clogging
UV Stable	Will not break down in direct sunlight
Net Free Area	18.4 Sq. In. inches per Linear Foot at the ridge

LAKESIDE™ CONSTRUCTION FASTENERS

FOLLOW US ON YouTube

To purchase contact us at:
1203 Goldsmith Road, Paragould, AR 72450
***870-586-0703** (office) \ **870-586-0643** (fax)*
***800-537-4160** (toll free)*
www.lakeside-fasteners.com

2-2023_V14